

# **TITLE OF THE INVENTION:**

## **TEMPORARY PROTECTIVE SHROUDS FOR PROTECTING WINDOWS AND FIXTURES DURING CONSTRUCTION**

### **BACKGROUND OF THE INVENTION**

#### **1. Field of the Invention**

The present invention relates generally to protective covers or masking shrouds that prevent paint, debris and the like from marring or defacing fixtures. More particularly, my invention relates to masking shrouds that can be actively deployed to at least temporarily protect window assemblies, bathroom fixtures, or other prefabricated modules installed during construction or remodeling.

#### **2. Description of the Related Art**

The modern building boom has been stimulated by a variety of factors, the most important one of which appears to be reduced interest rates. Residential and commercial construction rates have steadily increased over the last several years. During the last decade, sales of new residential units have approached or exceeded record levels almost every year. While the increased demand for housing has stimulated the residential construction industry, increasing jobs, profits and general activity in the area, time constraints placed upon the typical contractor have become burdensome. There is a constant rush to finish the job, as buyers are anxious to occupy new dwellings as soon as practicable. The construction boom has also created a skilled labor shortage, and in some areas, shortages of raw materials. As a result, construction costs have increased. At the same time, profit margins are constantly under threat. Successful contractors must work quickly and efficiently under constant pressure, while at the same time maintaining above-average quality control.

Partially as a result of the foregoing considerations, the use of various forms of prefabricated modules has become the norm in modern construction. For example, numerous bathroom and kitchen fixtures or modules exist. The trend is for units to be prefabricated as much as possible by the manufacturer, and to avoid the necessity of finishing or painting or

1 coating these fixtures once installed. Modern bath and shower modules, for example,  
2 comprise upright, fiberglass units that need merely be placed upon subframes and then  
3 plumbed adequately for use. Windows of varying sizes and configurations are sold as  
4 separate, largely aluminum “fin frame” units that are quickly fitted to pre-configured, wooden  
5 sub-frames crafted by the carpenter at the job site and nailed into place. A variety of single-  
6 hung and double-hung sash windows are available in numerous sizes, styles and  
7 configurations. The use of fixtures and increased modularization in general enhance the  
8 contractors’ speed and efficiency. At the same time, certain quality control problems have  
9 been aggravated.

10 Windows, bathroom fixtures and other modular items are installed midway through  
11 the construction process. Fin frame windows are nailed into place, and afterwards they are  
12 secured in place within the subframe by dry walling. During dry wall installation, numerous  
13 separate steps are completed. The trimming and fitting steps generate dust and debris. The  
14 finishing step involves the application of drywall “mud” to smooth border and transition  
15 areas. Wet mud can spill onto adjacent, unprotected fixtures or windows. Mudding is  
16 followed by subsequent taping and sanding, and the dust generated through the process can  
17 quickly accumulate on exposed surfaces and structures. Hand tools required for the process  
18 may be inadvertently dropped onto exposed items, and surface marring or structural damage  
19 is not uncommon. Numerous other construction processes that follow add to the mess. For  
20 example, spackled ceiling finishing can result in the widespread broadcasting of spackling  
21 compound. Unprotected fixtures and windows will require vigorous cleaning before the house  
22 can be sold.

23 Compounding the foregoing problems is that workers often stand or lean upon fixtures  
24 during construction. Unshielded contact with hand tools, such as those held in worker’s belts,  
25 or the application of force and weight prior to the completion of installation can cause  
26 damage. Dirty footprints can accumulate and add to the mess. Anything left unprotected is  
27 further subject to attack during the painting process, occurring during one of the last stages of  
28 construction.

29 Normally the tedious clean-up procedures executed during the end stages of interior  
30 construction mitigates the prior accumulation of dust, debris and grime. However, it can be  
31 very difficult to remove paint stains from some devices, and it is virtually impossible to

1 remove substantial surface blemishes caused by abrasion or impact with falling tools or  
2 equipment. Sometimes expensive shower or bathroom modules are inadvertently damaged by  
3 inappropriate worker short-cuts, exemplified for example, by the common practice of  
4 temporality placing hand tools and/or paint cans within shower stalls or upon window ledges.  
5 Sometimes even rigorous cleaning efforts cannot adequately cure surface blemishes or  
6 damage, and fixture replacement is necessitated.

7         The prior art has recognized the general problem outlined above. Diverse paint and  
8 masking devices that temporality cover various interior surfaces are known. Protective drop  
9 cloths are commonly deployed to prevent damage to objects in work areas. Large drop cloths  
10 deployed from rolls may be used on walkways, patios, decks, and carpeted areas. Standard  
11 drop cloths afford reasonable protection but they have certain disadvantages. For example,  
12 cotton drop cloths are not impermeable to certain fluids, so oil-based paint can pass through  
13 and deface the covered surface.

14         Window fixtures can be masked by paper or plastic sheeting secured to the frame  
15 periphery by adhesive tape. However, such conventional masking methods are inefficient.  
16 Substantial labor must be invested during both installation and subsequent removal. In the  
17 past, individual sashes have been covered by temporary plastic panels, which must be  
18 installed and then removed in separate time-consuming steps.

19         U. S. Pat. No. 2,922,392 shows an early, well-known window masking method.

20         U. S. Pat. No. 5,230,738 issued July 27, 1993 discloses a pliable masking device for  
21 covering a targeted area during construction activities.

22         U. S. Pat. No. 5,441,769 issued August 15, 1995 discloses a paint mask for shielding  
23 windows while painting the mullions disposed between adjacent panes. Each mask is made of  
24 flexible, plastic sheet, and is sized to cover an individual pane of glass.

25         U. S. Pat. No. 5,058,340 issued October 22, 1991 discloses a plastic film sheet and  
26 mounting method for shrouding large planar areas like ceilings. A plastic edge connector  
27 ultrasonically welded about the periphery of the region being protected grasps edges of the  
28 shroud. Heat is applied to tightly stretch the shroud into the desired position.

29         U. S. Pat. No. 5,266,390 issued November 30, 1993 discloses a plastic dropcloth  
30 comprising a layer of polypropylene film bonded to an intermediate layer comprising either  
31 polyethylene or polypropylene film. The polypropylene film absorbs and resists hydrocarbon

1 liquids such as paint, wood stains, paint thinners, solvents and the like. In manufacture, the  
2 layers are fusion bonded together via heating units and pressure rollers

3 U. S. Pat. No. 5,658,632 issued August 19, 1997 discloses a masking strip equipped  
4 with adhesive for affixation to various structures. The mask is first placed over an area to be  
5 protected, and a desired portion of the adhesive strip is peeled back to enable custom  
6 affixation.

7 U. S. Pat. No. 4,263,355 issued April 21, 1981 sets forth a paint shield for masking a  
8 carpet or floor edges. The paint shield is formed from sections of a flat strip of resilient  
9 material packaged in a roll. The strip is rolled flat and springs back to shape when unwound  
10 from the roll.

11 U. S. Pat. No. 6,143,392 issued November 7, 2000 discloses a drop cloth especially  
12 configured for railings and banisters. An elongated, protective cover is fabricated from a strip  
13 of plastic or treated canvas.

14 U. S. Pat. No. 6,165,269 issued December 26, 2000 presents a kit for masking door  
15 and room hardware during painting. A variety of masks are configured for specific pieces of  
16 hardware, such as door hinges, door knobs, dead bolts, wall outlets and electric switches. A  
17 tapered cross section portion of each mask creates a fine edge which closely fits into the joint  
18 between the hardware and the door or wall.

19 U. S. Pat. No. 5,468,538 issued November 21, 1995 disclose a paint masking kit for  
20 windows and a method for masking windows. The masking kit comprises a plurality of  
21 reusable window balance covers for covering a header and balance portions of a window and  
22 a predetermined amount of plastic sheet material for covering each sash. Reusable plastic  
23 sheet material is applied over glass portions of the window.

24 U. S. Pat. No. 5,816,305 issued October 6, 1998 discloses a method for protecting an  
25 object during application of a fluid onto a surface, and a drop cloth having a first layer made  
26 of non-woven fabric material and a second layer of plastic.

27 U. S. Pat. No. 5,330,814 issued July 19, 1994 describes a protective cover pad having  
28 a backing sheet with a layer of adhesive and a removable strip of a flexible foam material,  
29 which is peelable from the adhesive surface. The strip of foam-like material has a greater  
30 thickness than the backing sheet and a greater width than either of the side portions of the  
31 backing sheet.

1 U. S. Pat. No. 5,103,593 issued April 14, 1992 discloses a door shield for temporarily  
2 covering a door during construction. A polymeric rear layer mounts an accordion-pleated  
3 forward surface formed of parallel ribs to provide impact resistance. Magnetic and adhesive  
4 members are coextensively formed at a rear perimeter of the door for adherence of the  
5 structure to the door.

6 U. S. Pat. No. 4,921,028 issued May 1, 1990 discloses a door hardware cover that can  
7 protect knobs and locks. A plastic sheet is adhesively attached to the base of the door  
8 hardware.

9 U. S. Pat. No. 4,398,495 issued August 16, 1983 discloses a thin, sheet-like paint  
10 shield comprising intersecting longitudinal and transverse creases. The crease arrangement  
11 enables the shield to be conformed about irregular volumes such as corner moldings or the  
12 like. By flexing the shield about its longitudinal crease, the bent portion automatically snaps  
13 back into a coplanar relationship with the remaining portion of the sheet so that its maximum  
14 longitudinal length is again available for shielding while painting.

15 U. S. Pat. No. 5,042,656 issued August 27, 1991 provides a door-shield in the form of  
16 a disposable envelope that functions as a protective sheath. The door to be protected is in  
17 effect sandwiched between its sides. The envelopes are formed as large plastic paper sheaths  
18 and are pulled onto the edge of a door opposite the door edge hinged to the frame. Once  
19 painting or decorating is complete, the envelopes are removed and discarded.

20 U. S. Pat. No. 5,921,282 issued July 13, 1999 discloses a disposable protective cover  
21 for exposed plumbing fixtures.

22 In view of the foregoing, it is apparent that a low-maintenance, temporary protective  
23 shroud for the various fixtures or modules discussed, that may be easily deployed and then  
24 removed by the contractor when interior construction is completed, would be desirable. An  
25 adequate shroud must be light-weight, protective, durable, tear-resistant, and liquid-proof. It  
26 must not interfere with the ability of the contractor or subcontractors to efficiently carry out  
27 their missions. Preferably, a single size must fit a variety of applications, and quick  
28 adjustments to shroud size must be possible at the job site without time-consuming measuring  
29 and cutting. Once interior construction or remodeling is complete, the shroud must be  
30 removable as fast as possible.

31

## **BRIEF SUMMARY OF THE INVENTION**

This invention provides a shroud system for protecting window fixture, bathroom fixtures, shower modules, and other prefabricated items during construction.

My new protective shrouds are quickly fitted to conventional window assemblies, bathroom fixtures, prefabricated modules or the like. During the many facets of construction, any object upon which one of my shrouds has been deployed is isolated and protected from dust, debris, and inadvertent injury. Not only is cleanliness maintained, but damages from contact with humans or tools or spilled liquids like paint, dry wall mud, or the like is avoided. After interior construction is substantially completed, the shroud is easily and quickly removed simply by cutting, and after tearing away and discarding the shroud body, no trace is left of the shroud.

The preferred window shroud is generally rectangular, and is made from resilient plastic sheets of polypropylene or polyethylene. Preferably the shroud is translucent, so the window framework is clearly visible after installation. The preferred arrangement has a lower open port that is selectively blocked by a foldable panel. This panel may be temporarily disposed in an open configuration, exposing the port, by a set of magnets that hold it in a deployed position. The flexible ventilation panel is also translucent.

The shroud comprises a number of back-mounted adhesive tear-away strips that affix it to the window. When the tear away strips are removed, the exposed adhesive surface is pressed upon the window structure. However, to properly fit the window fixture to be protected, slight adjustments to shroud height and width may quickly be made, without time-consuming measuring or cutting steps. Importantly, the adhesive strip on the top rear of the shroud and at least one side strip are bifurcated. In other words, the composite strip along these regions is divided into two segments, with a seam or crease disposed therebetween. One piece of the strip comprises a corner segment, mounted at the rear of at one upper corner. The adjoining strip segments start proximate the corner segment, and extend substantially the entire length of the top or that side. The two "bifurcated" adhesive strip segments enable the gathering of sheet material by manually pinching the sheet together, to shrink it in width or length to fit the desired target window. Once installed, dry-walling may commence, and edge pieces of the shroud are thereby captivated and sandwiched permanently against portions of the window frame by various dry wall segments. After dry-walling, the exposed junction

1 between covered shroud and adjacent sheet rock portions may be cut. This junction is  
2 smoothed over and treated with dry-wall mud for cosmetic effects. The shroud may then be  
3 torn away, removed, and discarded. A clean, undamaged and unmarred window fixture  
4 remains.

5 Thus a basic object of my invention is to provide a low cost shroud for shielding,  
6 windows, fixtures, modules and the like from dust, debris and overspray during construction.

7 A related object is to isolate windows, modules, fixtures and the like from damages  
8 that might result from contact with workers, or miscellaneous construction tools used during  
9 construction.

10 It is also an object of the present invention to provide a new and useful method for  
11 protecting windows, various surfaces and fixtures from fluids including paint and other  
12 compounds or mixtures comprising hydrocarbon solvents.

13 Moreover, it is an important object of my invention to protect otherwise-exposed  
14 surfaces of windows from debris and damages that might occur during construction activities.

15 It is still another object of the present invention to provide a protective shroud for  
16 windows and bathroom fixtures that may be easily adjusted during installation to snugly fit a  
17 variety of sizes, shapes and configurations.

18 A related object of this invention to provide a protective shroud of the character  
19 described that may be quickly and easily removed once construction is substantially finished.

20 Another important object of my invention is to provide a protective shroud for  
21 windows of the character described that readily facilitates the temporary opening of sash  
22 windows, so that the workers may be provided with adequate ventilation, even though the  
23 shroud is properly in place protecting the fixture.

24 Yet another object it to provide a highly durable shroud of the character described that  
25 is light-weight, puncture-resistant, and rapidly deployable.

26 A related object of my invention is to provide a shroud that is highly drapable.

27 Another important object is to enable the installer to adjust shroud height and width  
28 quickly without time-consuming measuring or cutting steps.

29 Another object is to provide a shroud of the character described that, once removed  
30 from the window, is completely invisible, and leaves no trace of its former presence. It also  
31 an object of my invention to provide new and useful methods for protecting construction

1 items such as fixtures, modules, windows and the like through the shroud techniques  
2 described.

3 These and other objects and advantages of the present invention, along with  
4 features of novelty appurtenant thereto, will appear or become apparent in the course of the  
5 following descriptive sections.

## 6 **BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS**

7  
8 In the following drawings, which form a part of the specification and which are  
9 to be construed in conjunction therewith, and in which like reference numerals have  
10 been employed throughout wherever possible to indicate like parts in the various views:

11 FIGURE 1 is an exploded, fragmentary isometric view showing a double sash, fin-  
12 frame window partially installed within a sub-frame, with a window shroud constructed in  
13 accordance with the best mode of the invention situated proximate the window and ready for  
14 installation;

15 FIGURE 2 is a fragmentary, isometric view showing the double sash window of  
16 Figure 1 partially installed;

17 FIGURE 3 is a fragmentary, isometric view showing the double sash window of  
18 Figures 1 and 2, with my window shroud positioned upon the window fixture;

19 FIGURE 4 is an enlarged fragmentary, isometric view of the corner region of the  
20 window and its frame, with portions thereof broken away for clarity;

21 FIGURE 5 is a fragmentary isometric view similar to Figure 4, but showing the  
22 exposed top of the window and the top of the shroud;

23 FIGURE 6 is a greatly enlarged, fragmentary isometric view of the front left corner  
24 region of the window as seen in Figure 5, showing width and height adjustments, and with  
25 certain portions greatly exaggerated in size for clarity;

26 FIGURE 7 is a frontal isometric view of the preferred window shroud, with the lower  
27 panel closed, as it appears with preliminary width and height adjustments;

28 FIGURE 8 is a rear view of the preferred window shroud, showing the adhesive strips  
29 and tape used for affixation and fitting adjustments;

30 FIGURE 9 is an isometric view similar to Figure 8 showing the window shroud, with  
31 the lower panel deflected to an "open" position;



1           FIGURE 10 is an isometric view showing the window shroud properly fitted to a  
2 window, with the lower shroud panel folded upwardly to expose the lower window sash;

3           FIGURE 11 is an enlarged, longitudinal sectional view taken generally along line 11-  
4 11 of Figure 9, with portions thereof broken away for clarity or omitted for brevity;

5           FIGURE 12 is an enlarged sectional view taken generally along line 12-12 of Figure 9,  
6 with portions thereof broken away for clarity or omitted for brevity;

7           FIGURE 13 is an enlarged sectional view taken generally along line 13-13 of Figure 9,  
8 with portions thereof broken away for clarity or omitted for brevity;

9           FIGURE 14 is an enlarged plan view taken generally along line 14-14 of Figure 9,  
10 with portions thereof broken away for clarity or omitted for brevity;

11           FIGURE 15 is an enlarged, fragmentary sectional view taken generally along line 15-  
12 15 of Figure 4, with portions thereof broken away for clarity or omitted for brevity;

13           FIGURE 16 is an isometric view of a fiberglass tub and shower fixture that is to be  
14 installed according to the invention;

15           FIGURE 17 is a fragmentary isometric view of a protective shroud that is to be  
16 attached to the fixture of Figure 16;

17           FIGURE 18 is a fragmentary isometric view of a fiberglass tub and shower fixture  
18 that has my protective shroud installed;

19           FIGURE 19 is a fragmentary, enlarged and exploded isometric view showing the  
20 installed shroud; and,

21           FIGURE 20 is a fragmentary isometric view showing the shroud-equipped fixture  
22 being framed during installation.

## 23                           DETAILED DESCRIPTION OF THE INVENTION

24           Turning initially to Figures 1-6 of the appended drawings, my new protective window  
25 shroud has been generally designated by the reference numeral 30. It is adapted to be fitted to  
26 a conventional window assembly 32 during construction. Once fitted properly, as hereinafter  
27 described, frame construction around the window, including dry-wall construction and the  
28 like, proceeds non-destructively, and the window is protected from unwanted contact with dirt  
29 and debris. After interior construction is substantially completed, the shroud 30 may be  
30 quickly removed, revealing a clean and undamaged window fixture.  
31

1 For informational purposes, the window assembly 32 comprises a conventional dual  
2 sash, fin frame window 34. A generally rectangular window frame 36 is formed from  
3 extruded aluminum pieces in a desired configuration, with a conventional size and aspect  
4 ratio. The upper horizontal span has been designated by the reference numeral 37, and that  
5 spans' upper surface has been designated by the reference numeral 37A (Figs. 4 and 6). The  
6 flat, inwardly facing vertical surface of the upper horizontal span has been designated by the  
7 reference numeral 37B (Figs. 2, 4).

8 The leftmost vertical span has been designated by the reference numeral 39, and its  
9 outer surface has been designated by the reference numeral 39A (Figs. 4 and 6). Those  
10 familiar with the art will note that a thin, peripheral "fin" 40 is disposed at the exterior side of  
11 the window, comprising a vertical portion 40A (Figs. 4, 6) that borders span surface 37A, and  
12 contiguous and integral vertical portions 40B that adjoin surface 39A. This step-like, notched  
13 profile enables mounting within a receptive region of a wooden subframe to be described  
14 hereinafter. Fin 40 has a plurality spaced apart orifices 41 through which conventional nails  
15 43 (Fig. 4) may be driven to mount the assembly within the wooden subframe.

16 The window frame 36 houses a fixed upper sash 45, and a vertically displaceable  
17 lower sash 47. In some configurations, both the upper and lower sashes are displaceable.  
18 Each sash has a plurality of individual glass panes 50 disposed between alternate vertical  
19 mullions 52 and horizontal mullions 54 (Figs. 1 and 2). Of course it should be recognized that  
20 single pane sashes exist as well. Moreover, single sash units are common, and the invention  
21 has equal utility when used with various window units of multiple configurations and sizes.

22 The fin frame window 34 is seated within an appropriate subframe 60, framed with  
23 conventional wooden pieces recognized by those skilled in the art. An upper, horizontal  
24 header 64 forms the top of the subassembly. It comprises a pair of transversely extending,  
25 spaced apart and parallel two by ten pieces 63, 64 (Figs. 2, 4). A transverse two by four piece  
26 66 (Figs. 2, 4) extends across the bottom of the header 62, beneath pieces 63 and 64. When  
27 the window is nested into the subframe, the windows top surface 37A (Fig. 6) will snugly  
28 contact the underside of header piece 66. The bottom of the subframe 60 is formed by a lower  
29 two by four piece 68m (Fig. 2) which is spaced apart from and parallel with upper header  
30 pieces 63, 64 and 66.

1           The parallel, left and right sides 70, 71 respectively of the subframe 60 are made of  
2 twin, two by four cripples. For example, the left side 70 comprises an outer, vertical cripple  
3 73 that extends vertically between and beyond the upper and lower header pieces 66 and 68.  
4 However the inner cripple 74 is flushly parallel with outer cripple 73. Cripple 74 extends from  
5 lower, transverse header piece 68 to the underside of upper header piece 66 (Fig. 2). The fin  
6 frame 40 (i.e., Figs. 2, 6) will flushly abut cripple 40 in assembly; further, it will abut the  
7 vertical outer edge 39A (Fig. 6) of the window frame after assembly. Nails 43 (i.e., Fig. 2)  
8 will be driven through fin frame orifices 41 when the window unit is mated to the subframe  
9 60.

10           As best seen in Figure 4, after the window unit is seated within and fastened to the  
11 subframe 60, dry walling will commence. Portions of typical drywall are illustrated, for  
12 purposes to become clear later. There is a transverse piece of drywall 82 extending  
13 horizontally across the window, beneath the header 60. The inner edge of drywall header  
14 piece 82 abuts the exposed vertical surface 37B of the window previously discussed. It  
15 extends across the top of the window to complete the framing. A span of sheet rock 84  
16 oriented in the vertical plane extends across the side. Similarly, flat trim pieces 86 and 87  
17 complete the sheet rocking. Similarly, the remainder of the framing is bordered by the larger  
18 adjacent wall board segment 84.

19           The details relating to sheet rock construction techniques and dry-wall installation  
20 configurations will be appreciated by those with skill in the art; however, the point is that the  
21 shroud 30 unobtrusively fits in with the sheet rock process as hereinafter explained. As will  
22 also be appreciated, the sheet rock work and other constructions steps performed interiorly of  
23 the structure being erected generates considerable dust and waste products, and it is desirable  
24 to protect the aluminum window fixture to keep it as clean as possible. Shroud 30 has thus  
25 been configured to “interfit” within the framing and drywall structure just discussed. Stated  
26 another way, the shroud 30 mates with the window assembly 32 and, without hindering the  
27 normal construction routine, protects the window from damage and keeps it clean.  
28 Importantly the shroud 30 does not interfere with operation of the lower sash- i.e., when  
29 protected by the shroud during construction, the window may yet be opened if desired. When  
30 the necessary construction steps are substantially completed, the shroud is quickly removed as  
31 explained hereinafter.

1           With joint reference now directed to Figures 1 and 6-8, the preferred window shroud  
2 30 is generally rectangular, and is preferably made from resilient plastic, ideally  
3 polypropylene or polyethylene sheet. In the best mode the shroud is translucent, but in some  
4 circumstances darkly colored or opaque variations may be desirable. The top 100 is parallel  
5 and spaced apart from bottom 102, with the right and left sides 104, 106 respectively  
6 extending vertically therebetween. In the preferred embodiment the shroud 30 has a  
7 deflectable, lower ventilation panel 108 attached to it along crease 109 that covers an open  
8 port 110. This rectangular port 110 provides an opening for ventilation, needed when the  
9 window being covered is opened during construction. Optional ventilation panel 108 is also  
10 made of resilient and translucent plastic sheet. A pair of spaced apart magnets 112 and 113 are  
11 attached near the bottom of panel 108. A second pair of magnets 114, and 115 are disposed  
12 near the top of shroud 30, in similar spaced apart relation. Magnets 114, 115 are mounted with  
13 their magnetic polarity reversed, so they will attract and releasably hold magnets 112, 113  
14 when the ventilation flap is opened. When flap 108 is gently lifted up to expose the port 110,  
15 the panel magnets 112, 113 can be pushed into temporary binding contact with magnets 114,  
16 115 that will hold the panel open, as in Fig. 9. On the other hand, when the ventilation panel is  
17 “down” (i.e., the port 110 is blocked by panel 108), magnets 112, 113 are strongly attracted to  
18 magnets 117, 119 (Fig. 9). This third pair of magnets is spaced similarly to the others for  
19 alignment purposes, and is located near the bottom 102 of the shroud.

20           The shroud is preferably pressed upon and adhesively mounted to the window  
21 structure. A plurality of peel-away adhesive strips are formed at the back of the shroud along  
22 the top 100, bottom 102, and along sides 104, 106. To properly fit the window fixture to be  
23 shrouded, the installer must be able to make slight adjustments to shroud height and width,  
24 preferably without time-consuming measuring or cutting steps. Therefore an important height  
25 and width adjustment means incorporated into the preferred design.

26           Noting Fig. 8, there is an elongated peel-away adhesive strip portion 120 extending  
27 substantially along the length of the top 100. A similar corner portion 122 (Fig. 8)  
28 substantially completes the extent across the top back of the shroud, bordering portion 120  
29 and forming a small crease 125 therebetween. The combined total strip at the shroud top 100  
30 comprising portions 120 and 122 is thus “bifurcated” into two segments. Similarly there is a  
31 peel-away adhesive strip portion 128 aligned with left side 106 (Fig. 8), which borders corner

1 portion 122 along adjacent horizontal crease 129 (Fig. 8). As before, the combined total strip  
2 at the shroud side 106 comprising portions 122 and 128 is thus “bifurcated” into two  
3 segments. The crease or border between the strip portions makes folding or gathering easier  
4 during dimensional adjustments. However, the unitary adhesive strips 130, 132 (Fig. 8) at the  
5 bottom rear and right rear side of the shroud need not be bifurcated. Horizontal crease 129  
6 (Fig. 8) at the shroud rear is aligned with and parallel to elongated, horizontal gathered  
7 portion 129B (Fig. 6) at the front of the shroud, that results from pinching during dimensional  
8 adjustment. Similarly, vertical crease 125 (Fig. 8), that separates strip portions 122, 120, is  
9 coextensive with and parallel to the elongated, vertical gathered portion 125B (Fig. 6) at the  
10 front of the shroud in Fig. 8. The latter creases at the rear of the pinched, or gathered portions  
11 125B and/or 129B (Fig. 6) result from width or length adjustments, and their formation is  
12 aided by the fact that the strips are bifurcated i.e., the corner portion 122 may be deployed  
13 first while dimensional approximations are made mentally during prefitting. Then, when the  
14 approximately correct size is gauged, by manually pinching together and gathering the sheet  
15 material (i.e., changing the size of gathered regions 125B, 129B) strip portions 120 and 128  
16 may be deployed, first by removing their outer tape coverings, and then by pressing the  
17 exposed adhesive against the aligned window surfaces previously discussed.

18 In other words, when the shroud 30 is installed, the adhesive strips are used for  
19 mounting. The peel away covering 133 (Fig. 8) is removed as desired. Preferably the corner  
20 piece is activated first, and the shroud 30 is pressed up against the horizontal window span 37  
21 (Fig. 1) against the flat, exposed, vertically span surface 37B (Figs. 4, 6) of the window.  
22 When merely the corner of the shroud is thus attached, portions of the sheet material may be  
23 grasped and punched together, forming the gathered ridges 125B, 129B (Fig. 6) that “take in”  
24 material to contract the width or length as desired for the job site. By suitably pinching the  
25 sheet together to form these gathered regions 125B, 129B of varying dimensions, the shroud  
26 will thus be customized into an exact “fit.” Then the backing sheet on the longer adjacent  
27 adhesive strip portions 120, 128 (Fig. 8) may be removed for installing the shroud. Of course,  
28 adhesive strips 130, 133 may then be deployed in a like manner, so that the shroud 30 fits up  
29 against the window.

30 Noting Figures 3-5, the shroud is installed after the window fixture ( and after the  
31 window’s subframe is made) but before the sheet-rock is placed. It will be noted from Fig. 4

1 particularly that edges of the shroud 30 are captivated or sandwiched against the window  
2 structure by various sheet-rock pieces. For example, in Figure 4 edge portions of the shroud  
3 30 are covered by the edges of sheet rock pieces 82 and 87. Once internal construction is  
4 completed, the seam formed between the junction regions of the shroud and drywall pieces  
5 (such as pieces 82, 84 in Fig. 4) is cut manually by a suitable bladed tool, like a box-cutter.  
6 The exposed junction that has just been cut may be smoothed over by drywall mud. Then the  
7 remainder of the shroud is torn out of the fixture and discarded, yielding a clean, undamaged  
8 window. Afterwards, even a careful inspection of the window reveals no visible evidence that  
9 the shroud was used. In other words, the peripheral shroud segments left behind after cutting  
10 do not mar the appearance of the window assembly 32.

11 With reference to Figures 16-20, an alternative embodiment of my shroud system is to  
12 be described. The protective shroud 200 (i.e., Figs. 17-19) is adapted to be fitted to a  
13 conventional bathtub and shower fixture during its installation and subsequent construction  
14 work to prevent its surface from being marred or scratched by falling debris, paint cans, or by  
15 equipment including miscellaneous tools and supplies or the like placed upon it during  
16 construction. For example, a conventional prefabricated bath and shower assembly 202 (Fig.  
17 16) is to be protected by the shroud 200 which is protectively placed upon it prior to framing  
18 as hereinafter described. Once properly installed, fixture 202 is protected. And, as before,  
19 upon completion of the dwelling or room construction, shroud 200 is quickly removed and  
20 disposed of, revealing a clean and unblemished bathroom fixture 202.

21 The conventional bathroom fixture 202 (Fig. 16) comprises a conventional tub 204 of  
22 generally parallelepiped dimensions. Tub 204 has a bottom floor 206 surrounded by internal  
23 ends 208, and internal walls 210, the tops of which are surmounted by a circumferential ledge  
24 212. Outer, lower, rectangular tub surface 213 faces the viewer. The attached and adjacent  
25 shower casing 214 comprises spaced apart, upright walls 216, 218, and 221 that surround the  
26 lower tub 204. These walls rise upwardly to a circumferential upper ledge 225 that is adjacent  
27 to a surrounding, peripheral mounting flange 228. When the framing elements are thereafter  
28 deployed during fixture installation, they will abut ledge 225 and flange 228, as is well  
29 recognized in the art. Thus, as illustrated generally in Figure 20, fixture 202 will be flushly  
30 surrounded by conventional framing 222 and drywall construction 230 (Fig. 20). Substantially  
31 contemporaneously with framing, the fixture 202 will be plumbed. All of the latter

1 constructions operations generate appreciable dust and debris, and numerous finishing tools  
2 are used during the process. Without installing my shroud 200, the fixture can become marred  
3 or damaged.

4 The preferred shroud 200 is made of translucent plastic sheeting and shipped in  
5 packages of multiple disposable shrouds. As seen best in Figure 17, a typical shroud 200  
6 comprises adjoining, integral panels 233, 234 and 235. Panels 233 and 234 have top edges  
7 233A and 234A respectively, with outer terminal lateral edges 233B and 234B respectively.  
8 Inner panel 235 has an upper edge 235A (i.e., Fig. 17). These edges have first runs of  
9 removable, bifurcated adhesive tape strips 240, 241 (i.e., Fig. 19) that meet in a junction  
10 comprising a separation region 243. When peeled off from the broken connecting point at the  
11 junction region 243, the strips 240, 241 are peeled back and discarded, revealing an  
12 adhesively coated region 247 (Fig. 19) of the edges that is adapted to be affixed to the  
13 exposed fixture flange region 228. Concurrently with the removal of the bifurcated adhesive  
14 strips 240, 241, an intermediate area may be gathered to produce gathered flaps 250, that  
15 enable the user to quickly approximately adjust the length and width of the deployed shroud,  
16 so as to properly cover the fixture 202 for subsequent construction work. The outer lateral  
17 edges have a second set of tape runs, having a split junction forming a separation region 247  
18 between adjacent tape segments 248, 249. This enables quick access to the strip ends, so that  
19 the tape strips can be peeled away to expose an adhesive surface along both lateral vertical  
20 ends of the panels 233, 234 (Fig. 17). This enables gathered flaps 250A, 250B (i.e., fig 18) to  
21 be manipulated for adjusting the approximate vertical dimension of the shroud panels.

22 With construction substantially finished, immediately prior to dry wall caulking  
23 exposed edges, the shroud 200 may be cut along boundary 256 (i.e., Fig. 20) with an  
24 appropriate knife or box-cutter. Once ripped away and disposed of, the shroud yields a clean  
25 and unmarred fixture.

26 From the foregoing, it will be seen that this invention is one well adapted to obtain  
27 all the ends and objects herein set forth, together with other advantages which are inherent  
28 to the structure.

29 It will be understood that certain features and subcombinations are of utility  
30 and may be employed without reference to other features and subcombinations. This  
31 is contemplated by and is within the scope of the claims.

1           As many possible embodiments may be made of the invention without departing  
2 from the scope thereof, it is to be understood that all matter herein set forth or shown in the  
3 accompanying drawings is to be interpreted as illustrative and not in a limiting sense.

4           WHAT IS CLAIMED IS:

5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31